

\*\*\* SPARE PART\*\*\* SIMATIC S7-300, CPU 312C COMPACT CPU WITH MPI, 10 DI/6 DO, 2 FAST COUNTERS (10 KHZ), INTEGRATED 24V DC POWER SUPPLY, 32 KBYTE WORKING MEMORY, FRONT CONNECTOR (1 X 40PIN) AND MICRO MEMORY CARD REQUIRED



Figure similar

General information	
Hardware product version	01
Firmware version	V2.6
Engineering with	
• Programming package	STEP 7 V5.3 SP2 or higher with HW update
Supply voltage	
Rated value (DC)	Yes
• 24 V DC	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	Miniature circuit breaker, type C; min. 2 A; miniature circuit breaker type B, min. 4 A
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Digital inputs	

— Rated value (DC)	24 V
— Reverse polarity protection	Yes
Digital outputs	
— Rated value (DC)	24 V
— Reverse polarity protection	No
Input current	
Current consumption (rated value)	500 mA
Current consumption (in no-load operation), typ.	60 mA
Inrush current, typ.	11 A
$I^2t$	0.7 A <sup>2</sup> ·s
Digital outputs	
• from load voltage L+, max.	50 mA
Power loss	
Power loss, typ.	6 W
Memory	
Work memory	
• integrated	32 kbyte
• expandable	No
Load memory	
• Plug-in (MMC)	Yes
• Plug-in (MMC), max.	4 Mbyte
• Data management on MMC (after last programming), min.	10 y
Backup	
• present	Yes; Guaranteed by MMC (maintenance-free)
• without battery	Yes; Program and data
CPU processing times	
for bit operations, typ.	0.2 μs
for bit operations, max.	0.4 μs
for word operations, typ.	0.4 μs
for fixed point arithmetic, typ.	5 μs
for floating point arithmetic, typ.	6 μs
CPU-blocks	
Number of blocks (total)	1 024; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
DB	
• Number, max.	511; Number range: 1 to 511
• Size, max.	16 kbyte
FB	
• Number, max.	1 024; Number range: 0 to 2047
• Size, max.	16 kbyte

FC	
• Number, max.	1 024; Number range: 0 to 2047
• Size, max.	16 kbyte
OB	
• Number, max.	see instruction list
• Size, max.	16 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	1; OB 20
• Number of cyclic interrupt OBs	1; OB 35
• Number of process alarm OBs	1; OB 40
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	4; OB 80, 82, 85, 87
• Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
• per priority class	8
• additional within an error OB	4
Counters, timers and their retentivity	
S7 counter	
• Number	128
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	127
— preset	8
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
• Number	Unlimited (limited only by RAM capacity)
S7 times	
• Number	128
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	127
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	

• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)

## Data areas and their retentivity

retentive data area in total	all
Flag	
• Number, max.	128 byte
• Retentivity available	Yes; MB 0 to MB 127
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Number, max.	511; from DB1 to DB511
• Size, max.	16 kbyte
• Retentivity adjustable	Yes; via non-retain property on DB
• Retentivity preset	Yes
Local data	
• per priority class, max.	256 byte

## Address area

I/O address area	
• Inputs	1 kbyte
• Outputs	1 kbyte
Process image	
• Inputs	128 byte
• Outputs	128 byte
Default addresses of the integrated channels	
— Digital inputs	124.0 to 125.1
— Digital outputs	124.0 to 124.5
Digital channels	
• Inputs	266
— of which central	266
• Outputs	262
— of which central	262
Analog channels	
• Inputs	64
— of which central	64
• Outputs	64
— of which central	64

## Hardware configuration

Number of expansion units, max.	0
Number of DP masters	

• integrated	none
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	4
Rack	
• Racks, max.	1
• Modules per rack, max.	8
Time of day	
Clock	
• Software clock	Yes
• retentive and synchronizable	No
• Deviation per day, max.	15 s
Operating hours counter	
• Number	1
• Number/Number range	0
• Range of values	0 to 2 <sup>31</sup> hours (when using SFC 101)
• Granularity	1 hour
• retentive	Yes; Must be restarted at each restart
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• in AS, master	Yes
Digital inputs	
Number of digital inputs	10
• of which inputs usable for technological functions	8
integrated channels (DI)	10
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	10
— up to 60 °C, max.	5
vertical installation	
— up to 40 °C, max.	5
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V

• for signal "1"	+15 to +30V
<b>Input current</b>	
• for signal "1", typ.	9 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.3 / 3 / 15 ms
— Rated value	3 ms
for counter/technological functions	
— at "0" to "1", max.	48 µs
<b>Cable length</b>	
• shielded, max.	1 000 m; 100 m for technological functions
• unshielded, max.	600 m; For technological functions: No
for technological functions	
— shielded, max.	100 m
— unshielded, max.	not allowed
<b>Digital outputs</b>	
Number of digital outputs	6
• of which high-speed outputs	2
integrated channels (DO)	6
Short-circuit protection	Yes; Clocked electronically
• Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	L+ (-48 V)
Controlling a digital input	Yes
<b>Switching capacity of the outputs</b>	
• on lamp load, max.	5 W
<b>Load resistance range</b>	
• lower limit	48 Ω
• upper limit	4 kΩ
<b>Output voltage</b>	
• for signal "1", min.	L+ (-0.8 V)
<b>Output current</b>	
• for signal "1" rated value	500 mA
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	0.6 A
• for signal "1" minimum load current	5 mA
• for signal "0" residual current, max.	0.5 mA
<b>Parallel switching of two outputs</b>	
• for uprating	No
• for redundant control of a load	Yes
<b>Switching frequency</b>	
• with resistive load, max.	100 Hz

• with inductive load, max.	0.5 Hz
• on lamp load, max.	100 Hz
• of the pulse outputs, with resistive load, max.	2.5 kHz
<b>Total current of the outputs (per group)</b>	
<b>horizontal installation</b>	
— up to 40 °C, max.	2 A
— up to 60 °C, max.	1.5 A
<b>vertical installation</b>	
— up to 40 °C, max.	1.5 A
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Analog inputs</b>	
integrated channels (AI)	none
<b>Analog outputs</b>	
integrated channels (AO)	none
<b>Encoder</b>	
<b>Connectable encoders</b>	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
<b>Interfaces</b>	
Number of industrial Ethernet interfaces	0
Number of RS 485 interfaces	1; MPI
Number of RS 422 interfaces	0
<b>MPI</b>	
• Cable length, max.	50 m; without repeater
<b>1. Interface</b>	
Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	No
Power supply to interface (15 to 30 V DC), max.	200 mA
<b>Functionality</b>	
• MPI	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Point-to-point connection	No
<b>MPI</b>	
• Number of connections	6
• Transmission rate, max.	187.5 kbit/s

<b>Services</b>	
— PG/OP communication	Yes
— Routing	No
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
<b>Communication functions</b>	
PG/OP communication	Yes
<b>Global data communication</b>	
• supported	Yes
• Number of GD loops, max.	4
• Number of GD packets, max.	4
• Number of GD packets, transmitter, max.	4
• Number of GD packets, receiver, max.	4
• Size of GD packets, max.	22 byte
• Size of GD packet (of which consistent), max.	22 byte
<b>S7 basic communication</b>	
• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
<b>S7 communication</b>	
• supported	Yes
• as server	Yes
• as client	Yes; Via CP and loadable FB
• User data per job, max.	180 byte; With PUT/GET
• User data per job (of which consistent), max.	64 byte
<b>S5 compatible communication</b>	
• supported	Yes; via CP and loadable FC
<b>Number of connections</b>	
• overall	6
• usable for PG communication	5
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	5
• usable for OP communication	5
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	5



- usable for S7 basic communication
  - reserved for S7 basic communication
  - adjustable for S7 basic communication, min.
  - adjustable for S7 basic communication, max.
- usable for routing

2  
0  
0  
2  
No

### S7 message functions

Number of login stations for message functions, max.	6; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	20

### Test commissioning functions

Status block	Yes
Single step	Yes
Number of breakpoints	2

Status/control	
• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14

Forcing	
• Forcing	Yes
• Forcing, variables	Inputs, outputs
• Number of variables, max.	10

Diagnostic buffer	
• present	Yes
• Number of entries, max.	100

### Interrupts/diagnostics/status information

Diagnostics indication LED	
• Status indicator digital input (green)	Yes
• Status indicator digital output (green)	Yes

### Integrated Functions

Number of counters	2; 2 channels (see "Technological Functions" manual)
Counting frequency (counter) max.	10 kHz
Frequency measurement	Yes
Number of frequency meters	2; 2 channels up to max. 10 kHz (see "Technological Functions" manual)
controlled positioning	No
integrated function blocks (closed-loop control)	No

PID controller	No
Number of pulse outputs	2; 2 channels pulse width modulation up to 2.5 kHz (see Manual "Technological Functions")
Limit frequency (pulse)	2.5 kHz

#### Potential separation

##### Potential separation digital inputs

- |  |     |
|--|-----|
| • Potential separation digital inputs    | Yes |
| • between the channels                   | No  |
| • between the channels and backplane bus | Yes |

##### Potential separation digital outputs

- |  |     |
|--|-----|
| • Potential separation digital outputs   | Yes |
| • between the channels                   | No  |
| • between the channels and backplane bus | Yes |

#### Permissible potential difference

between different circuits	75 V DC/60 V AC
----------------------------	-----------------

#### Isolation

Isolation tested with	600 V DC
-----------------------	----------

#### Configuration

##### Configuration software

- |          |                              |
|----------|------------------------------|
| • STEP 7 | Yes; V5.3 SP2 with HW update |
|----------|------------------------------|

##### Programming

- |                                |                      |
|--------------------------------|----------------------|
| • Command set                  | see instruction list |
| • Nesting levels               | 8                    |
| • System functions (SFC)       | see instruction list |
| • System function blocks (SFB) | see instruction list |

##### Programming language

- |            |     |
|------------|-----|
| — LAD      | Yes |
| — FBD      | Yes |
| — STL      | Yes |
| — SCL      | Yes |
| — GRAPH    | Yes |
| — HiGraph® | Yes |

##### Know-how protection

- |   |     |
|---|-----|
| • User program protection/password protection | Yes |
|---|-----|

#### Dimensions

Width	80 mm
Height	125 mm
Depth	130 mm

#### Weights

Weight, approx.	409 g
-----------------	-------

last modified:

08/12/2017